# DID YOU KNOW?

about our...

NEW PRODUCT

# Grade 80 Eye Safety Hook

Eye safety hook locks when a load is applied to prevent the release of chains and lifting slings.

## EYE SAFETY HOOK
### POWDER COAT / HEC / GRADE 80

| Part | Qfind | Size | WLL | BL |
|---|---|---|---|---|
| | | M | (tonne) | (tonne) |
| ULHK08PSE-06 | **HSE6** | 6 | 1.12 | 4.48 |
| ULHK08PSE-08 | **HSE8** | 8 | 2.00 | 8.00 |
| ULHK08PSE-10 | **HSE10** | 10 | 3.15 | 12.60 |
| ULHK08PSE-13 | **HSE13** | 13 | 5.30 | 21.20 |
| ULHK08PSE-16 | **HSE16** | 16 | 8.00 | 32.00 |



## APPLICATIONS

- Use with Grade 80 lifting components
- Lifting with chains and synthetic slings

## FEATURES

- Conforms to AS 3776
- 100% magnaflux crack detection
- Safety hook prevents components from releasing if line becomes slack
- Back lever releases hook




## MARKINGS:

- **CE** (European Conformity)
- **WLL** (Working Load Limit)
- **Trace Code** (linked to certificate online)
- **Manufacturer's mark**

You can download this Test Certificate and/or Report from our website:

**hobson.com.au**

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

230215DYK